



**Industry leading performance in
ammonia detection technology**

Manning EC-F9-NH3 sensor / transmitter



Ammonia Specific

- Rapid response to ammonia
- Internal monitoring of 4/20 mA loop circuitry continuity

Versatility

- Can be used with any Honeywell Analytics readout
- Standard range of 100 ppm can be rescaled for higher ranges
- Provides a linear output of 4/20 mA as a function of refrigerant concentration

Easy Maintenance

- Quick and easy calibration
- Realtime calibration eliminates maintenance downtime

Long sensor life

- Quick and easy calibration

ATMOS™ Technology

- Allows for operation down to -50 F and in condensing humidity environments or during washdown
- Automatically adapts to its environment and provides accurate and reliable performance under the harshest conditions

SensorCheck™ Technology

- Checks operating parameters of sensors and sends a notification output signal if an anomaly is identified
- Tests the sensor every 24 hours for electrical viability
- Indication can be detected by a Manning gas monitor or PLC

Housing

- NEMA 1 #16 gauge heavy-duty steel enclosure
- Explosion-proof design available

The Manning EC-F9-NH3 with SensorCheck™ features industry-leading performance gas detection technology and adds a built-in system to monitor and predict the sensor's electrical viability.

Available with an optional LCD that allows real time display of gas concentration. The easy to read display allows for quick visual error events upon startup and troubleshooting and can be calibrated without a voltmeter. The EC-F9-NH3 with LCD is designed to work in the harshest environments including chemical washdown.

General Description

The Manning EC-F9-NH3 sensor consists of a pair of polarized electrodes isolated from the ambient air by a gas permeable membrane. As ammonia diffuses into the sensor, a redox reaction occurs, generating a current linearly proportional to ammonia gas concentration. Unlike many other ammonia sensors, this gas diffusion detector exhibits excellent zero and calibration stability over long periods of time. EC cells often last 3-4 years in the refrigerated environments of food processing and storage warehouses. This sensor can provide direct input into PLC's and computer control systems that accept a linear 4/20 mA signal either directly from the sensor or from any Manning multi-channel stand alone alarm consoles with relay or analog output.

Applications

- Bakeries
- Beverage, Bottling Plants
- Blast, Spiral Freezers
- Chemical Manufacturing
- Gas Bottling Plants
- Coolers
- Duct-Mounted Sensors
- Equipment Rooms
- Food Processing
- Fruit, Vegetable Processing
- Ice Cream Storage
- Penthouses
- Perimeter Monitoring
- Potable Water Plants
- Poultry, Meat, Fish Processing
- NOx Reduction (power plants)
- Refrigeration Systems
- Storage Freezers
- Turbine Inlet Cooling
- Wineries



EC-F9-NH3 with LCD option

Technical summary



General Specification	
Use	Electrochemical (diffusion) type sensor that works in conjunction with any Honeywell Analytics readout or alarm unit. Readouts have built in visual and audible alarms, as well as relay output for ventilation fan activation, central alarm tie-in, etc. The Manning EC-F9-NH3 can provide a linear 4/20 mA signal input into PLC's.
Common Operation	
Operation	In units without the optional LCD module, a group of LED's are installed to the PCB. In units with the optional LCD, two external push buttons, "Accept" and "Scroll" are used to navigate test functions and operating modes.
LCD display (optional)	2 line by 8 alpha numeric characters and continuous backlight
Output	Isolated 4/20 mA, 700 ohms max. at 24 VDC. Signal output reduces to 0.5 mA to indicate a fault condition. RS-485, Modbus RTU protocol
Accuracy	+/- 5% generally, but limited by available calibration gas accuracy. Enclosure contains no moving parts, contributing to accuracy levels.
Environmental IP rating	Indoor use, IP 44 in accordance with EN60529:1992
Operational	
Humidity	5-100% RH (condensing)
Temperature	-50°C to +120°C, ATMOS equipped enviro-adaptive technology required for refrigerated areas or outdoors
Sensor Pressure Limit	0-10 PSIG
Storage	-40°C to +80°C / -40°F to +176°F, 20 to 80%RH (non condensing)
Common Module	
Communication	4/20 mA output: #18/3 shielded cable (Belden 8770 or equal), cable runs < 1,500 ft. RS-485: for communication cable, use 24 AWG twisted pair, shielded (Belden #9841 or equal), cable runs up to 2,000 ft. For power cable use 14 AWG (Belden #5100UE or equal), cable runs up to 1,000 feet.
Power Source	24 VDC, 0.5 amp max.
Repeatability	+/- 2% full scale
Sensor Specifications	
Sensor Pressure	Limits 0-10 PSIG
Response Time	T50 = 10 seconds T100 < 1 second for concentration > 1% NH3
Ranges	0-100 ppm (standard) 0-250 ppm 0-500 ppm 0-1000 ppm
Sensor Viability Test	SensorCheck, an internal microprocessor determines the sensor's electrical viability every 24 hours. If the viability test fails, an 0.5 mA signal will indicate a fault. An internal light will show if a sensor is dried up or disconnected.
Enclosure	NEMA 1, gasketed, #16 gauge steel (standard). Stainless steel or explosion-proof designs, including modified enclosures for low temperatures, ventilation ducts, etc. are available.
Weight	3 lbs.

As world leaders in gas detection solutions, Honeywell Analytics' Manning range of gas detection systems has been designed to provide efficient, practical and cost-effective equipment to protect people from a variety of forms of hazardous gas and to efficiently monitor and control indoor air quality. The equipment is also simple to install and easy to operate and maintain.

The Manning range of fixed gas detection and accessories



Manning Vent Line



Manning AirScan iR



Manning GM-1



Manning GM-10



Manning GM-4000

Manning Line of Sensors

Designed for both industrial and commercial environments, the Manning line of sensors are produced to withstand the harshest of environments. The electrochemical and infrared sensors can be configured with the optional ATMOS[®] equipped technology that allows them to meet all of their performance specifications down to -50° F and in condensing humidity environments or during washdown.

Find out more

For more information on Honeywell Analytic's Manning line of products, visit www.honeywellanalytics.com or contact us at 800 444 9935

Customer business center

USA, Central and South America

Honeywell Analytics
23500 West 105th Street, MD 400
Olathe, KS
66061-6615
Tel: +1 913 894 1185
Toll free: +1 800 444 9935
Fax: +1 888 328 2417
detectgas@honeywell.com
www.honeywell.com

Customer business center

Canada

Honeywell Analytics
4005 Matte Blvd., Unit G
Brossard, QC, Canada
J4Y 2P4
Toll free: +1 800 563 2967
Tel: +1 450 619 2450
Fax: +1 888 967 9938
detectgas@honeywell.com
www.honeywell.com

Customer business centre

Europe and the rest of the world

Honeywell Analytics
Wilstrasse 11-U11
CH-8610 Uster
Switzerland
Tel: +41 (0) 44 943 4300
Fax: +41 (0)44 943 4398
gasdetection@honeywell.com
www.honeywell.com

Manning Controllers

Regardless of the number of sensors that need to be monitored, there is a Honeywell Analytics Manning controller system that will suit your needs. These multi-channel stand-alone monitoring/safety systems support up to ten (10) Honeywell Analytics gas detection sensors each and can interface with the plant central safety controls. Modular construction allows easy addition of up to forty (40) extra relay outputs and individual 4/20 mA signal output from each channel.



Manning AirAlert™ 96d

Multi-Channel Readouts

The Manning AirAlert 96d is designed for installation and operational simplicity for continuous monitoring and control of toxic gases, combustible gases and oxygen hazards. With a total of 96 gas sensors and relay modules linked to one controller, the Manning AirAlert 96d detection system represents the most affordable protection for your gas monitoring requirements.



Calibration Kit

The do-it-yourself solution for recommended calibration of Manning fixed line of gas detection products enables the product to be recertified for the required sensor recalibration. This easy to use kit contains everything needed for simple calibration including gas cylinders containing applicable gas, a calibration adaptor, flow meter, valve assembly, and tubing housed in a durable carrying case.

Honeywell